

## YK 系列圆振动筛

# YK Series Inclined Vibrating Screen

YK 系列圆振动筛是我公司吸收德国技术制造的高效振动筛。适宜采石场筛分砂石料，也可用于选煤、选矿、建材、电力及化工等行业。

YK Series Incline Vibrating Screen absorbs Germany technology, and is special designed to sieve different sizes of aggregate. It is also applied to coal dressing, ore dressing, building material, electric power and chemical industries.

### 特点及优势:

- 采用块偏心作为激振力，激振力强；
- 筛机横梁与筛箱采用高强度螺栓联接，无焊接；
- 筛机结构简单，维修方便快捷；
- 采用轮胎联轴器，柔性联接，运转平稳；
- 筛分效率高，处理量大，寿命长。

### Features and Benefits:

- High vibrating force with unique eccentric structure.
- The beam and case of the screen are connected with high strength bolts without welding.
- Simple structure, easy maintenance
- Adopt tire coupling, soft connection makes operation smooth.
- High efficiency, high capacity and durable.



### Technical Data

Model	Screen Deck	Installation Slope (°)	Deck Size (m <sup>2</sup> )	Vibrating Frequency(r/min)	Double Amplitude (mm)	Capacity (m <sup>3</sup> /h)	Motor Power (kw)
2YK1224	2	15	2.88	970	6~8	20~120	5.5
2YK1235	2	15	4.2	970	6~8	20~150	5.5
3YK1235	3	15	4.2	970	6~8	20~150	7.5
4YK1235	4	15	4.2	970	6~8	20~150	11
YK1545	1	15	6.75	970	6~8	22~150	11
2YK1545	2	17.5	6.75	970	6~8	22~150	15
3YK1545	3	17.5	6.75	970	6~8	22~150	15
4YK1545	4	17.5	6.75	970	6~8	22~150	18.5
YK1860	1	20	10.8	970	6~8	32~350	15
2YK1860	2	20	10.8	970	6~8	32~350	18.5
3YK1860	3	20	10.8	970	6~8	32~350	18.5
4YK1860	4	20	10.8	970	6~8	32~350	22
YK2160	1	20	12.6	970	6~8	66~720	18.5
2YK2160	2	20	12.6	970	6~8	66~720	22
3YK2160	3	20	12.6	970	6~8	66~720	30
4YK2160	4	20	12.6	970	6~8	66~720	30
YK2460	1	20	14.4	970	6~8	75~750	22
2YK2460	2	20	14.4	970	6~8	75~750	30
3YK2460	3	20	14.4	970	6~8	75~750	30
4YK2460	4	20	14.4	970	6~8	75~750	30
YK3060	1	20	17.4	970	6~8	200~900	30
2YK3060	2	20	17.4	970	6~8	200~900	37
3YK3060	3	20	17.4	970	6~8	200~900	45
4YK3060	4	20	17.4	970	6~8	200~900	45